



36 Draffin Road Hilton, New York 14468  
 Phone: 585-392-3434  
 Toll Free: 1-800-828-6351  
 Sales: sales@monroefluid.com  
 Technical: technical@monroefluid.com

## ASTRO-CUT BCL LF

### OVERVIEW

ASTRO-CUT BCL LF is a low foam heavy duty BIOSTABLE semi-synthetic general purpose metalworking coolant containing approximately 20% mineral oil. This product, when diluted with water, forms a translucent amber emulsion which offers excellent workpiece visibility, good lubricity, very low foaming and superior cooling. ASTRO-CUT BCL LF is designed for the machining and grinding of virtually all metals, except magnesium, and contains chlorine as an extreme pressure additive for greater lubricity.

### APPLICATIONS

ASTRO-CUT BCL LF is designed for use in metal removal operations such as all CNC milling, turning, drilling, tapping, and grinding. ASTRO-CUT BCL LF is also excellent on conventional machining processes and sawing applications.

### RECOMMENDED CONCENTRATION

Application	Concentration, %	Ratio	Refractometer
Milling, Drilling, Turning	5%	1:20	3.3
Centerless, ID, OD, Surface Grinding	4%	1:25	2.6
Tapping, Sawing, Reaming	10%	1:10	6.6

### MIXING

Concentration, %	4%	5%	6%	7%	8%	9%	10%
Ratio	1:25	1:20	1:17	1:14	1:12	1:11	1:10
Refractometer	2.6	3.3	4.0	4.6	5.3	5.9	6.6

### TYPICAL PROPERTIES

Appearance-Concentrate	Amber liquid
Appearance- Dilution	Translucent amber
Residual Film	Soft, fluid
pH @ 20:1	9.1 ± 0.2
Specific Gravity @ 60°F	1.02± 0.03
Lbs/Gallon	8.51 ± 0.1
Total Chlorine, wt %	1.0
Flash point, PMCC	None

Material Safety Data Sheets are available for all products.  
 All reasonable care has been taken to ensure  
 that the above information is accurate as of the date of printing.