

ASTRO-DRAW SYN FP

OVERVIEW

ASTRO-DRAW SYN FP is a heavy-duty synthetic, oil-free drawing, forming and stamping fluid, incorporating a blend of boundary and EP lubrication additives, in a water extendable package. ASTRO-DRAW SYN FP is a versatile drawing and stamping fluid that can be used neat or diluted with water. The film remaining after forming operations is easily removed with water or an alkaline cleaner. The product may be used on ferrous or non-ferrous metals.

| FEATUR | EQ 9. E | | 6 |
|--------|---------|--------|---|
| FEAIUR | E9 & E | DENELL | ັ |

- · Easily Removed With Water
- Mild Pleasant Odor
- \cdot Excellent Corrosion Inhibition
- Long Lasting
- \cdot Stable in Hard or Soft Water
- \cdot Operator Friendly
- · For Ferrous and Non-Ferrous Metals

Superior Lubricity

APPLICATIONS

ASTRO-DRAW SYN FP may be used for drawing and stamping operations where clean, oil-free parts are required for subsequent operations. ASTRO-DRAW SYN FP may be applied by brushing, dipping, spraying, rolling or other convenient method.

| Application | | Concentration, <mark>%</mark> | Ratio | | Refractometer |
|--|--------------------------|-------------------------------|--------------|------|---------------|
| Severe Drawing and Forming | | 10% - 20% | 1:10 to 1:5 | | 6.0 - 12.0 |
| Normal Applications | | 5% - 10% | 1:20 to 1:10 | | 3.0 - 6.0 |
| Light Applications, Roll Formin and Brass | ng C <mark>opp</mark> er | 4% - 5% | 1:25 to 1:20 | | 2.4 - 3.0 |
| MIXING | | | | | |
| Concentration, % | 4% | 5% | 7% | 10% | 20% |
| Ratio | 1:25 | 1:20 | 1:14 | 1:10 | 1:5 |
| Refractometer | 2.4 | 3.0 | 4.2 | 6.0 | 12.0 |

Appearance-ConcentrateAmber clear liquidAppearance- DilutionTranslucent/OpaquepH @ 10:18.7 ± 0.2Specific Gravity @ 60°F1.03± 0.03Lbs/Gallon8.59 ± 0.1Viscosity@40°130 cSt

Material Safety Data Sheets are available for all products. All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.