

## **Astro-Cut BCL**

## OVERVIEW

ASTRO-CUT BCL is a heavy duty BIOSTABLE semi-synthetic general purpose metalworking coolant containing approximately 20% mineral oil. This product, when diluted with water, forms a translucent amber emulsion which offers excellent workpiece visibility, good lubricity, and superior cooling. ASTRO-CUT BCL is designed for the machining and grinding of virtually all metals, except magnesium, and contains chlorine as an extremepressure additive for greater lubricity.

## APPLICATIONS

ASTRO-CUT BCL is designed for use in metal removal operations such as all CNC milling, turning, drilling, tapping, and grinding. ASTRO-CUT BCL is also excellent on conventional machining processes and sawing applications.

Application		Concentration		Ratio		Refractometer	
Tapping, Sawing, Rea	ming	10%		1:10		5.2	
General Machining		5%	6	1:	20	:	2.1
Grinding		49	6	1:25		2.6	
MIXING							
Concentration	4%	5%	6%	7%	8%	9%	10%
Ratio	1:25	1:20	1:17	1:14	1:12	1:11	1:10
Refractometer	2.1	2.6	3.1	3.6	4.2	4.7	5.2

Appearance-Concentrate		Amber Liquid
Appearance - Dilution		Translucent amber
Residual Film		Soft, fluid
pH @ 20:1		9.1 ± 0.2
Specific Gravity @ 60°F		1.0 ± 0.03
Lbs/Gallon		8.34 ± 0.1
Total Chlorine, wt %		1.0
Flash point, PMCC		None

Material Safety Data Sheets are available for all products. All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.