

## Astro-Cut HD XBP

## OVERVIEW

ASTRO-CUT HD XBP is a heavy duty BIOSTABLE semi-synthetic high pressure metalworking coolant. ASTRO-CUT HD XBP combines the superior chemical flexibility of synthetics with mineral oil and a chlorinated extreme-pressure additive. ASTRO-CUT HD XBP has exceptional foam control, hard water stability and tramp oil rejection. It provides outstanding extreme-pressure lubricity for machining and grinding virtually all metals, particularly Aluminum, Stainless Steels and other hard to machine alloys. ASTRO-CUT HD XBP is not recommended for use on Magnesium. ASTRO-CUT HD XBP is does not contain DCHA.

## APPLICATIONS

ASTRO-CUT HD XBP is designed for use in high and low pressure metal removal operations such as all CNC milling, turning, drilling, tapping, grinding and sawing.

Application		Concentration, 9	% Ratio		Refractometer		
Villing, Drilling, Turning	Drilling, Turning		6 1:20		0 4		.2
Centerless, ID, OD, Surface Grin <mark>ding</mark>		4%		1:25		3.4	
Tapping, Sawing, Reaming		10%		1:10		8.4	
MIXING							
Concentration, %	4%	5%	6%	7%	8%	<mark>9</mark> %	10%
Ratio	1: <mark>25</mark>	1:20	1:17	1:14	1:12	1:11	1:10
Refractometer	3.4	4.2	5.0	5.9	6.7	7.6	8.4

Appearance-Concentrate		Amber liquid
Appearance- Dilution		Translucent Amber
Residual Film		Soft, fluid
pH @ 20:1		9.3 ± 0.2
Specific Gravity @ 60°F		1.01± 0.03
Lbs/Gallon		8.43 ± 0.1
Total Chlorine, wt %		3 – 5% max
Flash point, PMCC		None

Material Safety Data Sheets are available for all products. All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.