



## Hysol AMG

High performance soluble metalworking fluid

### Description

Castrol Hysol™ AMG is a chlorine-free, heavy duty, emulsifiable fluid for machining and grinding steel, cast iron, stainless steels, aluminum, titanium and copper alloys. This low foaming fluid is specifically formulated for use with naturally soft or softened waters while still maintaining emulsion stability in hard waters. The oily concentrate of Hysol AMG is easy to mix with water, forming a stable, milky white, non-foaming emulsion that helps protect machines and manufactured parts from rust and stain while resisting the development of rancid odors and fungus.

Hysol AMG provides heavy duty extreme pressure lubricity without the use of chlorinated ingredients, making it an excellent choice for a wide variety of machining and grinding applications. These include broaching, tapping, reaming, deep hole drilling, multi-tool operations on CNC machines, centerless grinding and creep-feed grinding.

### Advantages

- Exceptional resistance to foaming
- Acceptable for use in most machining and grinding operations on a wide variety of metals.
- Good extreme pressure and boundary lubricity extends tool life and promotes better surface finishes
- Compatible with most machine tool paints and seals, helps keep machines and parts clean and in good operating condition
- Excellent emulsion stability in hard waters up to 115 gpg (2000 ppm)
- User friendly with a pleasant, mild odor

### Typical Physical Characteristics

	Unit	Test Method	Value
Appearance of Concentrate	-	Visual	Yellow fluid, slightly hazy
Appearance of Emulsion	-	Visual	Milky, opaque
pH of Concentrate	-	CN-TM-069	8.9 – 9.3
pH of Emulsion	@ 5%	CN-TM-069	9.1 – 9.7
Specific Gravity	@60°F (16°C)	Cn-TM-086	0.95 – 0.97
Bulk Density	Lbs/gal	-	8.1

## Recommended Concentrations

Grinding	3%
General Machining	4-8%
Drilling	5-10%
Reaming and Tapping	5-12%
Broaching	5-12%

## Concentration Control

Refractometer Reading	% Concentration
3.0	3.0
5.0	5.0
7.0	7.0
10.0	10.0

## Additional Information

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	ü	-	ü	ü	-

Hysol AMG  
28 Jun 2013  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600  
[www.castrol.com/en\\_us/b2b/home.html](http://www.castrol.com/en_us/b2b/home.html)