



Hysol MB 50

High performance soluble metalworking fluid

Description

Castrol Hysol[®] MB 50 is a high performance soluble metal working fluid recommended for machining all grades of aluminum as well as ferrous alloys. Hysol MB 50 provides the performance of heavy duty soluble oils without the unpleasant shop environments and high usage rates of traditional fluids. Hysol MB 50 is formulated without chlorine, sulfur and formaldehyde releasing agents. Its performance can exceed products which contain extreme pressure additives. The tight, stable emulsion of Hysol MB 50 provides extended system life and product stability.

Advantages

- Effective wetting properties maintains clean machines and components
- Stable fluid suitable for a wide range of water conditions
- Inhibits microbial growth to extend fluid life in central systems and individual sumps
- Low foaming in varying hardness water conditions
- Formulated without Formaldehyde releasing agents to comply with health and safety regulations
- Specifically designed to provide superior performance on aerospace and automotive aluminum

Typical Physical Characteristics

	Unit	Test Method	Value
Appearance of Concentrate	-	Visual	Slightly hazy to amber
Appearance of Emulsion	-	Visual	Tight emulsion, stable
pH of Emulsion	-	CN-TM-069	9.3 – 9.8
Specific Gravity	@60°F (16°C)	Cn-TM-086	0.94 – 0.96
Bulk Density	Lbs/gal	-	7.91
Nitrites	-	-	None
Chlorine	-	-	None
Phenols	-	-	None

Recommended Concentrations

Grinding: 3 - 5%*

Machining: 5 - 10%

Concentration should be maintained at 5 – 10%. Addition of product concentration in regular, standard additions will help maintain pH, bio-stability and additive levels.

*Systems using Hysol MB 50 should be maintained at a pH range of 8.8 – 9.3. Maintenance of pH level is important to control biological activity of coolant system.

Concentration Control

Hysol MB 50 Refractometer Factor = 1.0

To determine concentration multiply Refractometer BRIX reading by Factor

Additional Information

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	ü	-	ü	ü	-

Hysol MB 50

06 Jun 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html