

# **Product Data**

#### **Castrol llocut 154**

High-performance neat cutting oil

### **Description**

Castrol llocut<sup>™</sup> 154 is a chlorine- and heavy metal-free neat cutting oil.

#### **Application**

llocut 154 is designed for general machining of medium alloyed steel and non-ferrous metals.

	Cast Iron	Low-medium alloyed steel	High alloyed steel/nickel- chromium alloys	Titanium alloys	Aluminum alloys	Yellow metals
Honing/Superfinishing	-	-	-	-	1	-
Grinding	-	-	-	-	-	-
Drilling	-	-	-	-	-	-
Broaching/Gear manufacturing	-	-	-	-	-	-
General machining	1	✓	-	-	✓	✓

#### **Advantages**

- Advanced additive technology gives high extreme pressure (EP) lubricity properties, and can help lower production costs through extended tool life, improved surface finish and increased cutting speeds.
- Improved surface finish and increased cutting speeds help improve process efficiency.
- Multi-metal compatibility using our superior additive technology provides opportunity for product consolidation.
- · Our chlorine- and heavy-metal free formulation improves the environmental profile and reduces disposal costs.

## **Typical Characteristics**

Properties	Unit	Standard	<b>Data</b> Brown	
Appearance	Visual	Visual		
Viscosity @ 40°C	mm²/s	DIN 51562	35	
Viscosity@ 100°F	[SUS]	ASTM D 446	184	
Density @ 15°C	kg/m³	DIN 51757 ASTM D 1298	877	
	lbs/gal	Calculated	7.32	
Flashpoint COC	°C	ISO 2592	>190	
	°F	ASTM D 92	>370	
Copper corrosion	3 hr at 100°C	ISO 2160	1b	

	Ester	Active sulphur	Inactive sulphur	Phosphorous	Calcium	Chlorine	Zinc
Additives	+	-	+	-	-	1	-

Castrol Ilocut 154 18/12/2006, version 1.0

Castrol, llocut and the Castrol logo are trademarks of Castrol Limited, used under license.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563 Tel: (877) 641 1600 Fax: (877) 648 9801