



PRODUCT DATA SHEET

DRYDENE DIESELALL® HD ENGINE OILS

HEAVY-DUTY DIESEL ENGINE OIL



PRODUCT DESCRIPTION

DRYDENE DIESELALL® HD ENGINE OILS are premium low ash engine oils designed for use in older model diesel engines in both on-highway and off-highway applications as well as off-highway hydraulic systems requiring a 10W engine oil.

PRODUCT APPLICATION

DRYDENE DIESELALL HD ENGINE OILS are recommended for use in a variety of older model heavy-duty diesel and gasoline engine applications:

- Heavy equipment used on off-road mining, construction, agriculture and forestry operations
- Mixed fleets with on-highway diesel engines and smaller light-duty diesel and gasoline engines
- May be used in hydraulic and transmission systems where monograde engine oils are specified based on manufacturer guidelines

SPECIFICATIONS

API CF*
API CF-2* (SAE 30, 40, 50)
API SL

*- *obsolete service category*

FEATURES AND BENEFITS

DRYDENE DIESELALL HD ENGINE OILS are blended from premium base stocks and specific additives to provide dual-purpose performance in both crankcase and hydraulic systems.

- Detergent and dispersant additives help maintain engine cleanliness, suppress varnishing and aids in suspension of soot and contaminants in the oil.
- Robust anti-wear additives help extend regular drain intervals and overall engine life even in high operating temperature applications.
- Reliable performance in cold weather applications, especially in hydraulic systems (SAE 10W)



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	SAE 10W	SAE 30W	SAE 40W	SAE 50W
Viscosity @ 40°C, cSt	ASTM D445	37.0	88.0	133.0	192.0
Viscosity @ 100°C, cSt	ASTM D445	6.6	11.2	14.5	18.5
Viscosity Index	ASTM D2270	115	115	108	107
TBN, mgKOH/g	ASTM D2896	8.0	8.0	8.0	8.0
Pour Point, °C/°F	ASTM D97	-33/-27	-21/-6	-18/0	-12/10
Flash Point, °C/°F	ASTM D92	206/403	208/406	208/406	211/412

Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne assumes no responsibility for product misuse or improper application. For recommendations on safe handling of this product, refer to the Safety Data Sheet (SDS) at <https://www.drydene.com/pds-sds-sheets>. (Rev 1124-01)



RelaDyne, LLC. | 8280 Montgomery Road, Suite 101 | Cincinnati, OH 45236 | 1-888-830-3156 | WWW.RELADYNE.COM

