

Rustilo DW 4130

Dewatering corrosion preventative

Description

Rustilo™ DW 4130 is a soft film solvent deposited temporary corrosion preventive and dewatering fluid formulated to give excellent long-term indoor protection.

Applications

Rustilo DW 4130 is used for protecting components previously exposed to water-containing machines and grinding coolants, cleaners, or water rinses and also long term indoor protection of parts and components, which are stored under humid conditions.

Rustilo DW 4130 can be applied preferably by immersion, but if impractical, the fluid may be applied by brushing or spraying.

Advantages

- Based on solvent with aromatic content less than 10 ppm.
- Stable film characteristics reduce run-off loss and thus increase process reliability.
- Excellent long-term indoor protection.

Characteristics

	Unit	Test Method	Value
Appearance	-	Visual	Light brown fluid
Flash Point, PMCC	°C	ASTM D 93	> 38°C / 100°F
Film Type	-	-	Oily-greasy
Total Film Forming Content	%	-	22 – 23
Film Thickness	µm	-	1.3
Corrosion Protection, Indoor Storage	Month		18
Corrosion Protection, Outdoor Storage*	Month	-	3 – 6
Drying Time @ 20°C (to 95% solvent loss)	Min	-	75

*Assumes primary protection from the elements by tarpaulin or other form of cover

Additional Information

If required protective films of Rustilo DW 4130 can be removed by using a petroleum solvent or alkaline process cleaner, all available from Castrol.

Approval

Rustilo DW 4130 is approved by the following organizations:

- Cummins 102004
- Pratt & Whitney PMC 9119

Castrol, Rustilo, and the Castrol logo are trademarks of Castrol Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial