



Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 1 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

SECTION 1: Identification

Product Identifier

Product Name: Drydene AllTec GEO Low Ash SAE 40

Product code: D24040

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Engine Oil

Uses Advised Against: Any use than recommended above.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Reladyne, LLC

8280 Montgomery Road

Suite 1 Cincinnati, OH 45236

(888) 830-3156

sds@reladyne.com

Emergency Telephone Number:

United States

INFOTRAC

(800) 535-5053 (24/7)

SECTION 2: Hazard(s) Identification

GHS Classification:

Carcinogenicity, category 1B

Reproductive toxicity, category 2

Specific target organ toxicity - repeated exposure, category 1

Aspiration hazard, category 1

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways

Precautionary Statements:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 2 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P280 Wear protective gloves, protective clothing and eye protection.
P260 Do not breathe dust/fume/gas/mist/vapors/spray
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product
P308+P313 If exposed or concerned: Get medical advice.
P314 Get medical advice if you feel unwell.
P331 Do NOT induce vomiting
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.
P405 Store locked up
P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64-95
CAS Number: 64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	10-17
CAS Number: 8012-95-1	Paraffin oils	1-5
CAS Number: 68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	0.45-0.891

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 3 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

After Swallowing:

This product presents an aspiration hazard. If aspiration is suspected, seek emergency medical treatment. If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include shortness of breath, dry cough and irritation of the nose, eyes, lips, mouth and throat.

Delayed Symptoms and Effects:

May cause cancer. Insufficiently refined lubricant base oils with IP 346 \geq 3% produce tumors when tested in mouse dermal application tests. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Exposure may cause cancer. Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Causes damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

Symptoms of pulmonary edema may be delayed.

Immediate Medical Attention and Special Treatment

Specific Treatment:

Not determined or not applicable.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 4 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	8-Hour TWA-PEL: 2000 mg/m ³ ([500 ppm] Petroleum distillates, Naphtha; Rubber solvent)
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	8-Hour TWA-PEL: 5 mg/m ³ (Oil mist, mineral)
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	8-Hour TWA: 1600 mg/m ³ ([400 ppm] PETROLEUM DISTILLATES (NAPHTHA) (RUBBER SOLVENT))
	Paraffin oils	8012-95-1	PEL: 5 mg/m ³ (OIL MIST (MINERAL))

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 5 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	REL-TWA: 350 mg/m ³ (Petroleum distillates, naphtha [up to 10 hr])
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	IDLH: 1100 ppm (Petroleum distillates, naphtha)
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Ceiling Limit: 1800 mg/m ³ (Petroleum distillates, naphtha [15 min])
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	REL-TWA: 5 mg/m ³ (Oil mist, mineral [up to 10 hr])
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	15-Minute STEL: 10 mg/m ³ (Oil mist, mineral)
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	IDLH: 2500 mg/m ³ (Oil mist, mineral)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	REL: 5 mg/m ³ (Oil mist, Mineral [for up to a 10-hour workday during a 40-hour workweek])
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	STEL: 10 mg/m ³ (Oil mist, mineral)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	IDLH: 2500 mg/m ³ (Oil mist, mineral)
	Paraffin oils	8012-95-1	IDLH: 2500 mg/m ³ (Oil mist (mineral))
	Paraffin oils	8012-95-1	REL: 5 mg/m ³ (10-hour workday, Oil mist (mineral))
	Paraffin oils	8012-95-1	STEL: 10 mg/m ³ (Oil mist (mineral))
	United States(California)	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	8-Hour TWA-PEL: 5 mg/m ³ (oil [mineral] mist, particulate)
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	8-Hour TWA: 5 mg/m ³ (Oil (mineral) mist, particulate)
Paraffin oils		8012-95-1	8-Hour TWA: 5 mg/m ³ (Oil (mineral) mist, particulate)
ACGIH	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	8-Hour TWA: 5 mg/m ³ (mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-Hour TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction)
	Paraffin oils	8012-95-1	TLV-TWA: 5 mg/m ³ (8hr, Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction)

Biological Limit Values:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 6 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Amber Liquid
Odor	Slight Hydrocarbon
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	280 °C (536 °F)
Initial boiling point/range	400 °C (COC) (752 °F)
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 7 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Negligible
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	50 mm ² /s @ 40 °C
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

Strong oxidizing agents

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	oral	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: 2.18 mg/L (4 hr [aerosol])
	dermal	LD50 Rabbit: > 5000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
	inhalation	LC50 Rat: 2.18 mg/L (4 hr [aerosol])
Paraffin oils	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	oral	LD50 Rat: 2154 mg/kg
	dermal	LD50 Rabbit: >3160 mg/kg
	inhalation	LC50 Rat: >5 mg/L ([Dust/mist])

Skin Corrosion/Irritation

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 8 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment:

May cause cancer.

Product Data: No data available.

Substance Data:

Name	Species	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic		May cause cancer.
Distillates (petroleum), hydrotreated heavy paraffinic		May cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Group 3
Distillates (petroleum), hydrotreated heavy paraffinic	Group 3
Paraffin oils	Not Applicable
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Not Applicable

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 9 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Name	Classification
Distillates (petroleum), hydrotreated heavy paraffinic	Not Applicable
Paraffin oils	Not Applicable
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment:

Suspected of damaging fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment:

Causes damage to organs through prolonged or repeated exposure.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Assessment:

May be fatal if swallowed and enters airways.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	May be fatal if swallowed and enters airways.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 10 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	May be fatal if swallowed and enters airways.
Paraffin oils	Maybe fatal if swallowed and enters airways.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Fish LC50 Pimephales promelas: > 100 mg/L (96 hr [LL50 - mortality-QSAR data])
	Aquatic Invertebrates EC50 Daphnia magna: > 10,000 mg/L (48 hr [EL50 - mobility])
Distillates (petroleum), hydrotreated heavy paraffinic	Fish LC50 Pimephales promelas: > 100 mg/L (96 hr [LL50 - mortality])
	Aquatic Invertebrates EC50 Daphnia magna: > 10,000 mg/L (48 hr [EL50 - mobility, Read-across substance data])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Aquatic Invertebrates NOEC Daphnia magna: 10 mg/L (21 d [NOEL - reproduction])
	Fish NOEC Oncorhynchus mykiss: >=1000 mg/L (14 d [NOEL-mortality])
Distillates (petroleum), hydrotreated heavy paraffinic	Aquatic Invertebrates NOEC Daphnia magna: 10 mg/L (21 d [NOEL - reproduction])
	Fish NOEC Oncorhynchus mykiss: >= 1000 mg/L (14 d [NOELR-mortality, QSAR data])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Standard biodegradability studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), hydrotreated heavy paraffinic	Standard biodegradability studies are not applicable to petroleum UVCB substances.
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	The substance is not biodegradable. 0% degradation observed in water, measured by O2 consumption, after 28 days.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 11 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), hydrotreated heavy paraffinic	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.
Paraffin oils	The BCF values estimated for Mineral Paraffin Oil suggest some bioaccumulation potential for some of Mineral Paraffin Oil components. [BCF in fish: ≥ 500].
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	The substance has the potential to bioaccumulate significantly (log Pow=14.88 at 25 °C).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), hydrotreated heavy paraffinic	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.
Paraffin oils	Substance is slightly mobile with a high potential for adsorption to soil and sediment [Log Koc: >3].
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	The substance is moderately mobile, therefore, slight adsorption to soil is expected (Log Koc = 2.824).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Distillates (petroleum), solvent-dewaxed heavy paraffinic	Standard PBT studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), hydrotreated heavy paraffinic	Standard PBT studies are not applicable to petroleum UVCB substances.
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	The substance is not PBT.

vPvB assessment:

Distillates (petroleum), solvent-dewaxed heavy paraffinic	Standard vBvB studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), hydrotreated heavy paraffinic	Standard vBvB studies are not applicable to petroleum UVCB substances.
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	The substance is not vPvB.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 12 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory agencies. Dispose of in accordance with all applicable local, regional, state and federal regulations.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.16.2015

Page 13 of 13

Revision date: 12.13.2023

Drydene AllTec GEO Low Ash SAE 40

68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Listed
------------	---	--------

CERCLA:

68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Listed	NA
------------	---	--------	----

RCRA:

68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Listed	K039
------------	---	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	Listed
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	Listed
8012-95-1	Paraffin oils	Listed

New Jersey Right to Know:

64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	Listed
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	Listed
8012-95-1	Paraffin oils	Listed
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Listed

New York Right to Know:

68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Listed
------------	---	--------

Pennsylvania Right to Know:

64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	Listed
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	Listed
8012-95-1	Paraffin oils	Listed
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Listed

California Proposition 65: None of the ingredients are listed.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial Preparation Date: 05.16.2015

Revision date: 12.13.2023

End of Safety Data Sheet