# SAFETY DATA SHEET



Section 1. Identification		
Product name	Techniclean CPL	
SDS #	468675	
Historic SDS #:	11114	
Code	468675-US03	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	Cleaner. For specific application advice see appropriate Technical Data Sheet or consult our company representative.	
Supplier	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600	
EMERGENCY HEALTH INFORMATION:	+1-800-447-8735	
EMERGENCY SPILL INFORMATION:	+1-800-424-9300 (CHEMTREC USA) +1-703-527-3887 (CHEMTREC outside the US)	
Section 2. Hazar	ds identification	
OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CER 1910 1200)	

OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
GHS label elements	
Hazard pictograms	
Signal word	Warning
Hazard statements	Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.
Precautionary statements	
Prevention	Wear protective gloves. Wear eye or face protection. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	Defatting to the skin.

Product name Techniclean CPL	Product code	468675-US03	Page: 1/10
Version 3.01 Date of issue 10/25/2019.	Format US	Langua	ge ENGLISH

### Section 3. Composition/information on ingredients

Mixture

#### Substance/mixture

Alkalis and additives in aqueous solution.

Ingredient name	CAS number	%
Sistillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	≥25 - ≤50
Amine neutralized carboxylic acids	Not available.	≤10
Fatty acids, tall-oil, reaction products with ethanolamine, ethoxylated	61791-19-3	≤10
Alcohols, C16-18 and C18-unsatd., ethoxylated	68920-66-1	≤5
Boric acid	10043-35-3	≤3
(Z)-octadec-9-enol	143-28-2	≤3
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	≤3
Amine neutralised phosphoric acid esters	Not available.	≤3
3-Iodo-2-propynyl butylcarbamate	55406-53-6	<1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. In the event of any complaints or symptoms, avoid further exposure. Get medical attention.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water if person is conscious. Get medical attention if adverse health effects persist or are severe.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary Notes to physician Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed

	In case of inhalation of decomposition products in a fire, symptoms may be delayed.
	The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.

Product name Techniclean CPL	Product code	468675-US03 Page: 2/1	0
Version 3.01 Date of issue 10/25/2019.	Format US	Language ENGLISH	l i

### Section 5. Fire-fighting measures

-	_
Extinguishing media	
Suitable extinguishing media	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: phosphorus oxides metal oxide/oxides carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) sulfur oxides (SO, SO <sub>2</sub> etc.) nitrogen oxides (NO, NO <sub>2</sub> etc.)
Special protective actions for fire-fighters Special protective equipment for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.	
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".	
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for conta	ainment and cleaning up	
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.	

### Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Use only with adequate ventilation. Avoid contact of spilled material and runoff with soil and surface waterways.

Product name Techniclean CPL	Product code	468675-US03 Page: 3/10
Version 3.01 Date of issue 10/25/2019.	Format US	Language ENGLISH

### Section 7. Handling and storage

Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters Occupational exposure limits** Distillates (petroleum), hydrotreated heavy naphthenic ACGIH TLV (United States). TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction **OSHA PEL (United States).** TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 Amine neutralized carboxylic acids None. Fatty acids, tall-oil, reaction products with ethanolamine, ethoxylated None. Alcohols, C16-18 and C18-unsatd., ethoxylated None. Boric acid ACGIH TLV (United States). STEL: 6 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/2005 Form: Inhalable fraction TWA: 2 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/2005 Form: Inhalable fraction (Z)-octadec-9-enol None. Distillates (petroleum), hydrotreated heavy naphthenic ACGIH TLV (United States). TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction **OSHA PEL (United States).** TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 Amine neutralised phosphoric acid esters None. 3-lodo-2-propynyl butylcarbamate None. Appropriate engineering All activities involving chemicals should be assessed for their risks to health, to ensure controls exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Product nameTechniclean CPLProduct code468675-US03Page: 4/10Version 3.01Date of issue 10/25/2019.Format USLanguage ENGLISH

organisation for standards.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

concentrations below their respective occupational exposure limits.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne

# Section 8. Exposure controls/personal protection

•	• •	
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Individual protection measures		
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	Safety glasses with side shields.	
Skin protection		
Hand protection	Wear chemical resistant gloves. Recommended: Butyl gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.	
Body protection	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.	
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Respiratory protection	Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: half-face mask - inorganic gases/vapor filter (Type B) - particulate filter. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.	

# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Liquid.
Color	Amber. [Light]
Odor	Not available.
Odor threshold	Not available.
рН	9.1 [Conc. (% w/w): 5%]
Melting point	Not available.
Boiling point	Not available.
Flash point	Closed cup: >100°C (>212°F) [Estimated. Water content interferes with flash point determination.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.

Product name Techniclean CPL	Product code	468675-US03	Page: 5/10
Version 3.01 Date of issue 10/25/2019.	Format US	Languag	e ENGLISH

# Section 9. Physical and chemical properties

Vapor pressure	Not available.
Vapor density	Not available.
Density	<mark>≮1</mark> 000 kg/m³ (<1 g/cm³) at 15°C
Solubility	Soluble in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

## Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Avoid excessive heat.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials. Slightly reactive or incompatible with the following materials: acids.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Specific target organ toxicity (repeated exposure)

	Route of exposure	Target organs
Category 1		larynx
		exposureCategory 1Not determined

# Name Result Distillates (petroleum), hydrotreated heavy naphthenic ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	Routes of entry anticipated: Dermal, Inhalation.		
Potential acute health effects			
Eye contact	Causes serious eye irritation.		
Skin contact	Causes skin irritation. May cause an allergic skin reaction.		
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. May cause irritation to eyes, nose and throat due to exposure to vapor, mists or fumes.		
Ingestion	Irritating to mouth, throat and stomach.		
Symptoms related to the physic	al, chemical and toxicological characteristics		
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness		
Product name Techniclean CF	PL Product code 468675-US03 Page: 6/10		
Version 3.01 Date of issue 10	0/25/2019. Format US Language ENGLISH		

# Section 11. Toxicological information

Skin contact	Adverse symptoms may include the following: irritation redness dryness cracking
Inhalation	No specific data.
Ingestion	No specific data.
Delayed and immediate effect	s and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Potential chronic health effe	<u>cts</u>
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute to	icity estimates	
Route		ATE value
Øral		183235.98 mg/kg

# Section 12. Ecological information

**Toxicity** 

No testing has been performed by the manufacturer.

#### Persistence and degradability

Expected to be biodegradable.

#### **Bioaccumulative potential**

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (K <sub>oc</sub> )	Not available.
Mobility	Liquid. Soluble in water.
Other adverse effects	No known significant effects or critical hazards.

Product name Techniclean CPL	Product code	468675-US03	Page: 7/10
Version 3.01 Date of issue 10/25/2019.	Format US	Languag	je ENGLISH

### Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not av

Not available.

Not available.

Transport in bulk according to Annex II of MARPOL and the IBC Code

### Section 15. Regulatory information

U.S. Federal regulations	
United States inventory (TSCA 8b)	All components are active or exempted.
SARA 302/304	
Composition/information c	n ingredients
No products were found.	
<u>SARA 311/312</u>	
Classification	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
<u>SARA 313</u>	
Form R - Reporting requirements	This product does not contain any hazardous ingredients at or above regulated thresholds.
Supplier notification	This product does not contain any hazardous ingredients at or above regulated thresholds.
State regulations	
Massachusetts	The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL

Product name Techniclean CPL	Product code	468675-US03	Page: 8/10
Version 3.01 Date of issue 10/25/2019.	Format US	Language	e ENGLISH

# Section 15. Regulatory information

¥	-
New Jersey	The following components are listed: BORATE COMPOUNDS, Inorganic
Pennsylvania	None of the components are listed.
California Prop. 65	
This product does not red	quire a Safe Harbor warning under California Prop. 65.
Other regulations	
Australia inventory (AICS)	At least one component is not listed.
Canada inventory	At least one component is not listed.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	At least one component is not listed.
Philippines inventory (PICCS)	At least one component is not listed.
Taiwan Chemical Substances Inventory (TCSI)	Not determined.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

### Section 16. Other information

#### National Fire Protection Association (U.S.A.)



#### **History**

<u>HISTOLY</u>	
Date of issue/Date of revision	10/25/2019.
Date of previous issue	07/23/2019.
Prepared by	Product Stewardship
Key to abbreviations	<ul> <li>ACGIH = American Conference of Industrial Hygienists</li> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>CAS Number = Chemical Abstracts Service Registry Number</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</li> <li>IATA = International Air Transport Association</li> <li>IBC = Intermediate Bulk Container</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>OEL = Occupational Exposure Limit</li> <li>SDS = Safety Data Sheet</li> <li>STEL = Short term exposure limit</li> <li>TWA = Time weighted average</li> <li>UN = United Nations</li> <li>UN Number = United Nations Number, a four digit number assigned by the United</li> <li>Nations Committee of Experts on the Transport of Dangerous Goods.</li> <li>Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64742-61-4, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1</li> </ul>

✓ Indicates information that has changed from previously issued version.

Notice to reader

Product name Techniclean CPL	Product code	468675-US03	Page: 9/10
Version 3.01 Date of issue 10/25/2019.	Format US	Language	ENGLISH

### Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.