



Previous Name: Shell Tonna T

# Shell Tonna S2 M 32

• *Excellent Separation from Coolants*

## Machine tool slideway oils

Shell Tonna S2 M oils are specially designed for the lubrication of machine tool slides, tables and feed mechanisms. Their enhanced tackiness and stick-slip characteristics combine to offer superior frictional performance on slideways. They are specially recommended in cases where high exposure to soluble cutting fluids exist.

### DESIGNED TO MEET CHALLENGES

#### Performance, Features & Benefits

- **Ready separation from water-miscible cutting fluids**  
Separates completely and immediately from water-miscible metalworking fluids allowing easy removal by skimming. This helps to achieve longer coolant life, better cutting performance and to reduce Health & Safety issues.
- **Good slideway adhesion**  
Provides very effective adhesion to slideway surfaces, resisting wash-off by metalworking fluids and thus reducing oil consumption and giving more uniform working condition for the machine.
- **Good frictional properties**  
“Stick-slip” problems are overcome allowing more accurate positioning. This provides benefits of improved finished surface quality and dimensional accuracy of work pieces.
- **Good anti-wear performance**  
Provides anti-wear protection for slideways, gears, bearings and hydraulic system components.
- **Excellent corrosion prevention characteristics**  
Provides effective prevention of machine tool surfaces and components in the presence of water-miscible cutting fluids.

#### Main Applications



- **Machine tool slideways, tables and feed mechanisms**  
Developed for use on a wide range of materials used for machine tool slideway surfaces, including cast iron and synthetic materials.  
Shell Tonna S2 M oils can be used also in the hydraulic and gearboxes system although in such applications Shell Tonna S3 M oils are generally preferable.  
The lower viscosity grades are intended for horizontal slide lubrication (Shell Tonna S2 M 32 or 68). For vertical slides use Shell Tonna S2 M 220.

#### Specifications, Approvals & Recommendations

- Fives Cincinnati P-50 (ISO 220), P-47 (ISO 68), P-53 (ISO 32)
- ISO 19378 / ISO 6743-13 GA and GB DIN CGLP
- CGLP Slideway Oils against DIN 51502

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

#### Typical Physical Characteristics

Properties			Method	Shell Tonna S2 M 32
ISO Viscosity Grade			ASTM D2422	32
Kinematic Viscosity	@104°F	mm <sup>2</sup> /s	ASTM D445	32
Kinematic Viscosity	@212°F	mm <sup>2</sup> /s	ASTM D445	5.4
Viscosity Index			ASTM D2270	100
Density	@15°C	kg/m <sup>3</sup>	ASTM D1298	870
Flash Point (Cleveland Open Cup)			ASTM D92	419

Properties		Method	Shell Tonna S2 M 32
Pour Point	°F	ASTM D97	-22

These characteristics are typical of current production. While future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.Shell.com/>

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

### Additional Information

- **Advice**

Product recommendations for applications not covered here may be obtained from your Shell representative.