

Twin Specialties Corporation

11730 Walton Road, Suite 207 Blue Bell, PA 19422 O: (610) 834-7900 F: (610) 834-7903 sales@gemini-twin.com

HEAVY-DUTY TUBE DRAWING LUBRICANT

TWIN DRAW 1599

Twin Draw 1599 is a water-based and heavy-duty synthetic lubricant engineered for operations such as piercing, blanking, perforating, forming, drawing and stamping of carbon steel, galvanized steel, stainless steel, brass and aluminum. The high film strength reduces friction and heat, and provides anti-wear protection.

Twin Draw 1599 is non-staining and non-corrosive. When left on parts, the residual lubricant can be welded through without excessive smoking or interference with the integrity of the weld. The residual film also provides excellent protection from rust and oxidation.

OPERATIONAL DATA

Light Forming, Stamping & Blanking	5 - 15%
Moderate Drawing, Perforating & Piercing	15 - 30%
Heavy Forming, Drawing & Stamping	30 - 100%

TYPICAL PHYSICAL PROPERTIES

Appearance Bulk Density pH, Concentrate Flash Point Viscosity, cPs, 40 C Viscosity, SUS, 104 F Transparent, Amber Liquid 8.89 8.2 - 8.4 None 140 - 160 695

FEATURES AND BENEFITS

- Totally Synthetic, No Mineral Oils
- Non-Chlorinated
- Sulfur-Free
- Hard Water Tolerant
- Reduces Burrs
- Environmentally Sound Formulation
- Cleans with Water or Mild Detergent
- Clean and Low-Foaming
- Weld Through Residual Film
- True Solution, Will Not Bind Filters
- Superior Wetting and Detergency
- Eliminates Many Disposal Problems
- Inhibits Corrosion and Oxidation
- Provides Excellent Tool Life
- Cool Operating Temperatures
- Very Effective Combination of Extreme Pressure Additives

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use.