

Twin Kool 2695

WATER-SOLUBLE SYNTHETIC COOLANT

TWIN KOOL 2695

Twin Kool 2695 is a full-synthetic, heavy-duty, water-soluble coolant that is engineered for machining and grinding operations utilizing cast iron, stainless steel, carbon steel, alloy steels and nickel alloys.

Twin Kool 2695 is formulated with full-synthetic lubricants, inhibitors, advanced polymers and detergents to obtain optimum metal removal capabilities, excellent and prolonged tool life as well as superior corrosion inhibition. Its highly detergent, transparent solutions remain fresh and clean for extended sump life.

RECOMMENDED CONCENTRATIONS

General Machining	4 - 8%
Severe Machining	8 - 12%
Rough & Finish Grinding	3 - 6%

TYPICAL PHYSICAL PROPERTIES

Appearance	Transparent, Amber Liquid
Specific Gravity @ 60°F	1.07
Bulk Density	8.96 lbs/gal
Flash Point	None
pH, 5% Mix	9.7

FEATURES AND BENEFITS

- Full Synthetic; No Mineral Oil
- No Nitrites, Sulfur, Phenols, Heavy Metals, or Silicones
- Effectively Inhibits Corrosion & Rust
- Residual Film is Non-Sticky
- Highly Detergent Formulation
- Rejects Tramp Oil & Settles Fines
- Reduces Build-Up of Cast Iron Smut
- Alcohol and Solvent Free
- Low-Foaming up to 2,400 PSI
- Non-Misting Formulation
- Transparent Solutions Allow Clear Visibility of Work Pieces
- Engineered for Central Systems

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use.



Twin Specialties Corporation
11730 Walton Road, Suite 207
Blue Bell, PA 19422
O: (610) 834-7900
F: (610) 834-7903
sales@gemini-twin.com
twin oils.com