

Twin Kut 160

NEAT CUTTING OIL

TWIN KUT 160

Twin Kut 160 is a non-chlorinated, mildly sulfurized straight oil cutting fluid that is engineered for machining operations like tapping, turning, drilling, cutting, gear hobbing and broaching on difficult-to-work-with ferrous and nonferrous alloys.

Twin Kut 160 is formulated with premium base oil, select EP additives, robust fatty compounds and effective corrosion inhibitors, providing efficient heat dissipation, superior surface finishes, extended tool life and anti-weld characteristics.

OPERATIONAL DATA

All Operations	Use as Received
Viscosity, SUS, 100°F	< 20
Flash Point, C.O.C.	298°F, Minimum

TYPICAL PHYSICAL PROPERTIES

Appearance	Transparent Yellow Liquid
Odor	Mild, Characteristic
Specific Gravity, 60°F	0.889
Bulk Density	7.412 lbs./gal.
Solubility in Water	Insoluble

FEATURES AND BENEFITS

- Non-Chlorinated Cutting Fluid
- Mildly Sulfurized (Active)
- All-Purpose Machining
- Premium Base Oils
- Select EP Additives
- Superior Surface Finishes
- Extended Tool Life
- Anti-Weld & Anti-Foam
- Effective Corrosion Protection
- Environmentally Responsible

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use.



Twin Specialties Corporation
11730 Walton Road, Suite 207
Blue Bell, PA 19422
O: (610) 834-7900
F: (610) 834-7903
sales@gemini-twin.com
twin oils.com