

Twin Rust Preventative 121

RUST INHIBITOR AND PREVENTATIVE

TWIN RUST PREVENTATIVE 121

Twin Rust Preventative 121 is a general-purpose and low-viscosity, mineral oil-based rust preventative capable of providing long-term indoor storage protection to highly finished surfaces. The residual film is easily removed with alkaline cleaning solutions.

Twin Rust Preventative 121 is particularly effective at preventing dark surface stains due to direct part contact under conditions of high humidity, as well as condensation and/or a contaminated atmosphere (e.g. fork truck exhaust gases, acidic mists, etc.).

OPERATIONAL DATA

All Operations	Use as Received
Indoor Storage Protection	Up to 3 years
Humidity Cabinet Performance (ASTM D1748)	60 days, Min.

TYPICAL PHYSICAL PROPERTIES

Appearance	Amber Oil
Specific Gravity, 60°F	0.921
Viscosity, SUS, 100°F	125 - 145
Pour Point	-20°F, Max
Flash Point, COC	280°F, Min.

FEATURES AND BENEFITS

- Complete Penetration into Metal Pores to Insure Optimum Protection
- Low-Viscosity Formulation
- Minimizes Dripping
- Up To 3 Years Indoor Protection
- 60+ Days Humidity Protection
- Easily Applied With Brush, Swab, Immersion or Spray Equipment

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use.



Twin Specialties Corporation
11730 Walton Road, Suite 207
Blue Bell, PA 19422
O: (610) 834-7900
F: (610) 834-7903
sales@gemini-twin.com
twin oils.com