

# Twin Vanishing Oil 92

## DRAWING AND STAMPING OIL

### TWIN VANISHING OIL 92

Twin Vanishing Oil 92 is an evaporative lubricant designed for use on aluminum, steel and copper. This product is used as received and can be used for stamping, drawing, expanding, end-forming and cutting. This product is formulated with food status components, which promotes high operator acceptance. The additive system is ashless and burns clean in brazing and welding operations. This product is paintable when left on stamped parts.

The outstanding physical characteristics of this product coupled with the cost /performance function ratio, justify looking at replacing your present stamping lubricant. To obtain samples and pricing information contact our customer service representatives.

#### OPERATIONAL DATA

All Operations	Use as Received
Flash Point, C.O.C.	142°F
Viscosity, cSt, 40°C	2.45
Viscosity, SUS, 100°F	34

#### TYPICAL PHYSICAL PROPERTIES

Appearance	Clear, Colorless Liquid
Odor	Characteristic
Specific Gravity, 60°F	0.764
Bulk Density, lbs/gallon	6.36



Twin Specialties Corporation  
11730 Walton Road, Suite 207  
Blue Bell, PA 19422  
O: (610) 834-7900  
F: (610) 834-7903  
sales@gemini-twin.com  
twin oils.com

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use.