

# Twin Spindle Oil 10

## SPINDLE OIL

### TWIN SPINDLE OIL 10

Twin Spindle Oil 10 is a premium performance, mineral oil-based lubricant engineered for use in high-speed spindles and machine tools, among other industrial applications. It is formulated with high-quality, low-viscosity base oils, select anti-wear additives and effective corrosion inhibitors providing rust and oxidation protection.

#### OPERATIONAL DATA

Viscosity, cSt, 40°C	10
Viscosity, cSt, 100°C	2.62
Flash Point, ASTM D92	379°F, Minimum

#### TYPICAL PHYSICAL PROPERTIES

Appearance	Amber Liquid
Odor	Characteristic
Specific Gravity, 60°F	0.831
Bulk Density	6.928
ISO Viscosity Grade	10

#### FEATURES AND BENEFITS

- Premium performance
- Efficient corrosion protection
- Effective water separation
- Helps reduce deposits
- Improves life of equipment
- Resists emulsion formation
- Efficient foam resistance
- Readily separates from water



Twin Specialties Corporation  
11730 Walton Road, Suite 207  
Blue Bell, PA 19422  
O: (610) 834-7900  
F: (610) 834-7903  
sales@gemini-twin.com  
twin oils.com

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use.