

Twin Rainkote 100

Twin Rainkote 100 is an oil based rust preventive used for the protection of steel or cast iron parts during indoor storage for a period of up to one year. This dual purpose product can be used straight for full protection or as an emulsion for cost effective parts protection. The oily film deposited by Rainkote 100 is self healing and lubricating making it ideal for the storage of parts prior to assembly.

Features and Benefits

- Oily film is lubricating to aid in subsequent assembly of parts
- Self healing film continues to provide protection after handling
- Contains no solvents reducing odor and fire concerns
- Residual film is easily removed with alkaline cleaners
- ASTM D-1748, >35 DAYS / FAIL (used straight)
- ASTM D-1748, 15 DAYS/FAIL (10% emulsion)

Typical Properties

Appearance	Dark Amber liquid
Bulk Density	7.5 lbs/gal
Solubility	Emulsion
Flash Point	315 °F
Viscosity	200 - 275 SUS @ 100°F

Application Procedure

Twin Rainkote 100 is normally used full strength but can be diluted with equal parts solvent (mineral spirits or similar) to reduce viscosity and film thickness. It can be applied by spray, or immersion. Rainkote 100 can be removed with an alkaline cleaning solution. Consult Material Safety Data Sheet for a complete description of proper handling procedures.