



Twin Specialties Corp.

Oils & Chemicals for Industry
15 East Ridge Pike
Conshohocken, PA 19428

(610) 834-7900

FAX (610) 834-7903

TWIN RUST PREVENTIVE #200

Twin Rust Preventive #200 is a non staining oil based rust preventive used for the protection of steel during indoor storage for a period of up to one year. It is specifically designed for the protection of stacked or coiled steel in steel mills and is used in four high temper mills. Twin Rust Preventive #200 leaves a thin oily film which is self healing and easily removed with alkaline cleaners.

FEATURES and BENEFITS:

- . Non staining for use in coil lines
- . Contains no solvents reducing odor and fire concerns
- . Displaces water for application over wet surfaces
- . Residual film is easily removed with alkaline cleaners
- . Protects both steel and galvanized steel surfaces
- . Contains no barium or other heavy metals

TYPICAL PROPERTIES:

| | |
|--------------|---------------------|
| Appearance | Brown liquid |
| Bulk Density | 7.5 lbs./gallon |
| Solubility | Insoluble |
| Flash Point | 300 F |
| Viscosity | 100-125 SUS @ 100 F |

APPLICATION PROCEDURE:

Twin Rust Preventive #200 is used full strength and can be applied by spray, or immersion. The product displaces water and so there is no need to dry the surface prior to application. Twin Rust Preventive #200 can be removed with an alkaline cleaning solution.

Consult Material Safety Data Sheet for a complete description of proper handling procedures.