

Product Data

Variocut™ G 572

Heavy Duty Grinding Oil

Description

Castrol Variocut™ G 572 (previously called Grinding Oil™ 1572) is a heavy duty oil which can be used in all types of grinding applications where high surface finish is important. This product contains a very high additive package which will provide exceptional boundary lubrication in the most difficult operations.

Application

Variocut G 572 can be used in all types of thread, tap, gear and form grinding where requirements are extremely critical.

Advantages

- Uniquely compounded to give increased lubrication and surface wetting
- Provides minimal heat generation resulting in reduced discoloration and problems with heat checks
- Provides excellent wheel support, thus maintaining wheel form and final work piece finish and accuracy
- Recommended for use with cubic boron nitride grinding wheels
- Superior performance regardless of type of thread or form grinder

Typical Characteristics

Name	Method	Units	Variocut G 572
Appearance of Concentrate	CN-TM-007	Visual	Black opaque oil
Copper corrosion	CN-TM-020	-	4
Flash Point (COC)	CN-TM-039	-	360 - 370°F
Specific Gravity	CN-TM-084	60°F / 15.6°C	0.89 - 1.0
Viscosity Kinematic 40C	CN-TM-101	cSt	45 - 55

Subject to usual manufacturing tolerances.

Additional Information

F	-at	Chlorine	Sulphur
	ü	-	ü

This product was previously called Grinding Oil 1572. The name was changed in 2015

Variocut™ G 572 24 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600 www.castrol.com/en_us/b2b/home.html